





[条码网首页](#)
[条码网地图](#)
[条码新闻](#)
[联系我们](#)

[关于公司](#)
[条码产品](#)
[自主开发](#)
[应用方案](#)
[下载中心](#)
[条码知识](#)
[人才招聘](#)
[在线解答](#)


上海条码




先进的条码设备


专业的条码解决方案

全国统一服务热线 400-1199-021

www.tiaoma.org.cn

[条码产品](#)
当前位置: [条码产品](#) > [条码打印机](#) > [韩国woosim条码打印机](#) > [PORTI-SD40条码打印机](#)

条码打印机

- [美国Intermec条码打印机](#)
- [日本Tec条码打印机](#)
- [美国Zebra条码打印机](#)
- [日本Sato条码打印机](#)
- [日本Ring条码打印机](#)
- [美国Datamax条码打印机](#)
- [日本Citizen条码打印机](#)
- [日本Shinsei条码打印机](#)
- [日本Toshiba条码打印机](#)
- [美国Printronix条码打印机](#)
- [台湾Godex条码打印机](#)
- [台湾TSC条码打印机](#)
- [韩国Woosim条码打印机](#)
- [德国CAB条码打印机](#)

条码扫描器

数据采集器

条码软件

条码检测仪

条码标签

条码碳带

条码打印机配件

无线条码产品



Woosim PORTI-SD40 条码打印机

Features

- Pocket size (97 x 109 x 44.7mm)
- Light weight (350g) for true mobility
- Serial Impact DOT Matrix
- 40Columns (180dots/line)
- 50mm Wide Paper Width
- Battery Indicator
- UART or TTL, Bluetooth Ver2.0 Interface
- Support text and graphic printing
- Easier maintenance with self-diagnostics
- Free fall: 1 meter onto concrete (option 1.5 meter)
- Microsoft Windows ME / XP / 2000 / VISTA OS compatible

Specification


Item	Specification
Printing Method	Serial Impact DOT Matrix system
Printing direction	Uni-directional printing
Inking	Dedication ink ribbon cartridge (black or purple) (4+0.5)×8 Font, 40columns
Character size	[6×8, 7×10, 8×8, 8×9, 10×12]
Optional Characters	Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request.
Characters per line	40columns (4x8 Font)
Paper width	46.8mm, 180dots/line
Print feed pitch	3.52mm (10dot lines)
Paper supplied	57.5mm, Ordinary paper or specified pressure sensitive copying paper
Barcode	1-dimension : Code128, EAN 128, Code39, I2/5, Code93 UPC, EAN, KAN, JAN, CODABAR 2-dimension : PDF417, QR Code, DATA Matrix
Black mark	Support black mark detection
Printing speed	1.8 line/sec ± 20%
Dimensions	97 x 109 x 44.7mm
Weight	350g (Including battery & roll paper)
Interface	UART or TTL, Bluetooth Ver2.0
Receive buffer size	10K bytes
Battery	Rechargeable 7.4V DC 1,100mAh (Li-ion)
Battery duration	1 hour continuous printing
AC adapter	Input (100~250V AC, 50~60Hz) Output (8.4V DC / 0.8A), 4 hours full charge time
Operating temperature	-10° C~50° C
Storage temperature	-10° C~70° C
MCBF (Mean Cycle Between failure)	Head 1.0 million lines

销售热线

- 上海条码:021-51088451
- 广州条码:020-11381938
- 珠海条码:0756-2157363
- 深圳条码:0755-31866102
- 中山条码:0760-4194055
- 东莞条码:0755-51866036
- 北京条码:010-61126024
- 济南条码:0531-71754213
- 四川条码:待建中
- 沈阳条码:待建中
- 佛山条码:待建中
- 西安条码:待建中
- 长春条码:待建中
- 哈尔滨条码:待建中
- 武汉条码:待建中
- 厦门条码:待建中
- 兰州条码:待建中

热销推荐

- CASIO dt-940数据采集器
- symbol MC3090数据采集器
- symbol LS1203条码扫描器
- symbol LS9208条码扫描器
- symbol LS4208工业条码扫描器
- symbol LS3478无线条码扫描器
- symbol LS3008工业条码扫描器
- zebra 105s1工业条码打印机
- zebra 888TT商业桌面条码打印机

版权所有 © 上海条码网 

电话: 021-51088451 51088452 传真: 021-50935062

地址: 上海市浦东大道1097弄15号楼4E室 邮编: 200135 邮箱: mail@tiaoma.org.cn